

120°C/160°C双温型水循环模温机(中国首创单泵浦双温机)

DUAL-TEMPERATURE WATER CIRCULATION CONTROLLER OF 120°C/160°C

- 精密成型的最佳选择,以单马达提供两种不同循环水温控制公母模具为不同温度,而得到最佳成型品质要求.
- The best choose of precision molding Offer dual different temperature for mold with single motor.
- 高科技的结晶
- ASSOCIATED HIGH TECHNOLOGY.
- 设计先进
- ADVANCED DESIGNING.
- 让您精确掌握模具温度.
- PRECISELY POSSESSED MOLD TEMPERATURE CONTROLLER.

产品特点 Features:

- 采用单马达双温泵,可提供两组不同的温度控制,节省电能与空间
- This type can provide two different temp. for ulation controller.
- 采用意大利制『MERI』马达,提供高压,减少温差,节省电能.
- Adopting "MERI" motor from Italy, ensuring high pressure, providing temperature error reducing and saving power.
- 日本『OMRON』温控器,触摸式数字显示微电脑双组 P.I.D,精确控制在±1 °C内.
- Originally Japanese made "OMRON" temperature controller, P.I.D control and digital touch pad. Also it" s high precision±1 °C
- 采用日本[FUJI]、[OMRON]、意大利[ODE]、[OR].
- Electric parts use[FUJI]、[OMRON]、[ODE]、[OR]
- 专利分离式控制箱设计,完全断绝水气、油气、热量侵入,延长电气零件寿命.
- Separately controlled box patently designed. Insulates the invading of moisture and thermal energy, thus extending the time span of electricity parts.
- 连锁防错电路及实用故障指示,完整保护模温机稳定工作,维修保养无需专业人员,.
- Chained anti-mistaken circuit and realistically malfunctioned instruction, entire protection of mold temperature controller en-ensure the steady working conditions.
- 采用 304 不锈钢一体成型无缝管,减少管阻及锈垢.
- 316 stainless steel integrated pipelines for less pipe resistance and rust.

规格表 SPECIFICATIONS

机型	Model	DT-120	DT-160
使用电源	POWER SUPPLY	AC3 ϕ 380V 50HZ OR OTHER	AC3 ϕ 380V 50HZ OR OTHER
温控范围	Temperature range	室温+5°C~120°C	室温+20°C~160°C
温控精度	Temp. control accuracy	P. I. D \pm 1°C	P. I. D \pm 1°C
传热媒体	Heat transfer medium	水 CLEAN WATER	水 CLEAN WATER
冷却方式	Cooling method	直接冷却 DIRECT	间接冷却 INDIRECT
泵浦马力	Motor capacity	2HP	2HP
模 具 一	加热能力	Heating capacity #1	6KW/9KW
	最大流量	MAX FLOW RATE #1	50L/MIN
	最大压力	MAX PRESSURE #1	4KG/CM ²
模 具 二	加热能力	Heating capacity #2	6KW/9KW
	最大流量	MAX FLOW RATE #2	50L/MIN
	最大压力	MAX PRESSURE #2	4KG/CM ²
最大电力消耗	TOTAL POWER	13.5KW/19.5KW	13.5KW/19.5KW
警报功能	Alertfunction	缺相/反转/缺水/超温/超载/超压	缺相/反转/缺水/超温/超载/超压
冷却水配管	Cooling water pipe	1/2"	1/2"
循环水配管	Circulation water pipe	3/8"×4进4出*2组	3/8"×2进2出*2组
外型尺寸	LxWxH(CM)	75×36×78	83×38×88
重量	Weight	70KG	95KG

●以上规格如有变更,恕不另行通知,以实机为准. ●特殊规格及多机一体机型可另设计制造.Special design request.